

# Low-Noise 1.6L Benchtop Centrifuge With 6000rpm Max Speed And 4x400ml Capacity

### **Basic Information**

- Place of Origin:
- Brand Name: MKE
- Certification: CE,ISO13485,ISO9001,SFDA

1

CHINA

TDZ5-WS

Negotiable

Wooden Box

100 set/month

- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time: 7-15 work days
- Payment Terms: L/C,D/A,D/P,T/T,Western Union,MoneyGram
- Supply Ability:



### **Product Specification**

Product Name:	Low-Noise 1.6L Benchtop Centrifuge With 6000rpm
Applications:	Clinical Diagnostics, Veterinary Medicine, Pharmaceutics, Environmental Analysis, Industrial Production, Universities And Research Facilities
• Max Speed:	6000 Rpm
• Max RCF:	4752xg
<ul> <li>Max Capacity:</li> </ul>	4*400ml
• Time Range:	1min-99min Adjustable
Matched Rotors:	Fixed Angle Rotors, Swing Rotor And Microplate Rotor
• Display:	LCD
<ul> <li>Noise(dBA):</li> </ul>	≦58dB(A)
<ul> <li>Dimension(mm):</li> </ul>	600x440x360mm
Warranty:	1 Year Warranty For The Whole Machine, 3



More Images





Years Warranty For The Compressor And 5



## Description

TDZ5-WS Benchtop Centrifuge, a fusion of cutting-edge technology and exceptional capacity. It comes equipped with a variety of swing-out and fixed-angle rotors, complemented by an array of buckets and adapters, accommodating tubes and flasks ranging from 2 ml to 400 ml, including microtiter and deepwell plates.

Wide Compatibility: With its versatile accessories, it seamlessly caters to applications in clinical diagnostics, veterinary medicine, pharmaceutics, environmental analysis, and industrial production. It's also ideal for use in universities and research facilities.

Powerful Centrifugal Force: Achieves a maximum Relative Centrifugal Force (RCF) exceeding 4752 xg, ensuring efficient separation and processing across a multitude of samples.



# **Technical Specifications:**

Speed range(rpm)	0-6000rpm adjustable	Speed accuracy	±10rpm
Max Capacity(ml)	4*400ml	RCF range (xg)	0-4752xg adjustable
Display	LCD	Time range	1min-99minutes
Noise(dBA)	≦58dB(A)	Acceleration /Deceleration rates	1 10
Dimension(mm)	600x440x360mm	Motor	Frequency Converter motor
Net weight(without rotor)	40KGS	Power supply	AC220V,50HZ,10A,5 70W

## **Key Features:**

Robust Construction: Crafted from high-quality steel, including a blast-proof steel chamber and autoclaveable 304# stainless steel, ensuring durability and resistance to disinfectants.

Efficient Operation: Offers 10 acceleration rates and 10 braking ramps to prevent secondary sedimentation, ensuring superior centrifugation results.

Precision Control: Microprocessor-controlled with a frequency conversion A.C. motor drive, offering accurate and efficient centrifugation processes.

Intuitive Interface: The LED display showcases vital parameters, including Speed, Timer, RCF, Rotors, Program (Memory), Acceleration & Deceleration details, and Error Codes, enhancing operational clarity.

User-Friendly Design: Featuring a dual-layer sealing ring for enhanced lid and instrument sealing, alongside programmable memory storing up to 30 programs. Adapters ranging from 0.5 ml to 500 ml provide versatile usage.

Safety First: Complies with international safety regulations (e.g., IEC 61010). Equipped with electrical lid interlock, automatic lid-locking during rotor run, emergency lid-lock release during power failure, and a gas hinge for lid drop protection.

Reliable Performance: Boasts automatic troubleshooting capabilities, displaying error codes and alarms on the screen. Operates quietly, generating noise levels below 58 decibels even at maximum rotational speed.

No.	Item	Capacity	Max.speed	Max.RCF	Note
NO.1	Angle rotor	12×5-10-15ml		4.500	PP/PC tube
Adapter	· ·	12×2ml	6000r/min	4588xg	
NO.2	Swing rotor	Steel frame rotor		4752xg	
	Swing frame	4×100ml	-5000r/min		PP/PC tube
	Swing frame	4×50ml	-		PP/PC tube
	Adapter	4×15/10ml			PP/PC tube
	Swing rotor	Steel frame rotor		3041xg	
	Swing frame	4×2×100ml	1		PP/PC tube
	Swing frame	4×2×50ml	1		PP/PC tube
NO.3	Adapter	4×2×15/10ml	1		PP/PC tube
	Swing frame	4×8×15/10/5ml	4000r/min		PP/PC/Vacuum blood collection tubes
	Rack 4×12	4×12×5/2ml			Vacuum blood collection tubes
NO.4	Swing rotor	4×18×2/5ml	4000r/min	2773xg	Vacuum blood collection tubes
Swing bu NO.5 Adapter	Swing bucket	4×400ml	- 4000r/min -	3049xg	Square bucket
	Adapter	4×16×5/2ml			Vacuum blood collection tubes
*	Adapter	4×9×15/10ml			PP/PC tube
••	Adapter	4×4×50ml			PP/PC tube
	Adapter	4×100ml			PP/PC tube
NO.6	Swing bucket	4×250ml	4000r/min	3049xg	Round bucket
	Adapter	4×9×5/2ml			Vacuum blood collection tubes
	Adapter	4×5×15/10ml			PP/PC tube
	Adapter	4×50ml			PP/PC tube
	Adapter	4×100ml			PP/PC tube
	Adapter	4×9×1.5ml			PP/PC tube
NO.7	Microplate rotor	2×2×96 hole	4200r/min	2860×g	Square bucket
	Adapter	2×32×1.5ml	1		PP/PC tube

## Matched Rotors(MKE can produce custom accessories upon request)



#### WHY CHOOSE US

- Direct from the Manufacturer: Enjoy competitive pricing on all our products.
- Certified Excellence: Experience premium quality with our CE and ISO certified products.
- Customization at Its Best: Benefit from our robust OEM and ODM capabilities tailored to your specific needs.
- Reliable Production and Delivery: Trust us for guaranteed on-time production and delivery of your orders.
- **Comprehensive Support:** Rely on our comprehensive after-sales service, including complimentary product accessories.
- Expertise You Can Trust: We stand behind our 15 years of experience in R&D and production of medical centrifuge machines.



## **Our Factory Introduction**

We have a standardized production workshop operated by a dedicated team that ensures quality in every laboratory centrifuge and lab equipment we produce. Our R&D division includes design engineers, technology specialists, qualified experts, and process control managers. Following a strict quality control system, our specialists oversee the entire production process, from design and R&D to testing, production, quality inspection, and packaging.

• Specialize in centrifuges.

- With decades of experience, we've exported to 80+ countries.
- Proven Reputation: SGS and Intertek inspected, underlining our reliablity.
- Manufacturing Capabilities: 6 floors, 3000 sqm each, dedicated to manufacturing and quality control.



## MKE Exhibition



## Packaging & Delivery

MKE centrifuges are securely packaged in wooden cases or carton boxes, selected according to the weight and size of the goods. This ensures they are delivered in excellent condition to customers worldwide.



After-Sale WARRANTY



## <u>FAQ</u>

#### Q: How long is the production lead time?

A: Within 7-15 workdays after receiving deposit.

#### Q: What's your warranty?

A: All MKE products have ONE year warranty, five-year motor warranty. We won't charge clients any money for repairing the machine during one-year warranty time, the freight is also on us.

#### Q: How about the sample of MKE Centrifuge?

A: We could send you the samples but the freightand the sample are charged.

#### Q: Which kinds of Certificate would you have?

A: ISO9001, ISO13485, CE

#### Q: Do you offer centrifuges with voltage and plug options suitable for my country/region?

A: Yes, we provide centrifuges with various voltage and plug options to meet different country/region requirements. Please let us know your specific needs, and we will ensure compatibility.

#### Q: Are there customized options available for specific applications?

A: Absolutely! We offer customization options to meet specific application needs. Let us know your requirements, and we will tailor the centrifuge accordingly.

MKE	Professional Centrifuge Manufacturer	Michael Laboratory Ir	nstrument Co.,Ltd.
<b>()</b> +86-1	7775883371	Shirley@mke-lab.com	e mkecentrifuge.com
MKE Building, Sanhe Zhihui Industrial Park, Guyuan Road No. 426, Changsha High-techDevelopment Zone, Hunan, China			